

200 Amp, single phase MIG welder with 2 roll wire feed system and semi-synergic control panel. Controlled by microprocessor, set up is quick and easy with the machine controlling wire speed, this function avoids complex set up and ensures optimum welding performance.

PRODUCT

In « Synergic » mode, setting is fast and simple. The Micro processor controller will automatically set the optimum wire speed. This avoids complex set-up and ensures optimum welding parameters.

HIGH PERFORMANCE SINGLE PHASE

Rectified current smoothed by capacitors giving produces:

- Optimum fusion
- Reduced spatter

CAPACITOR INSIDE

3 FUNCTIONS AVAILABLE

- **Normal**
- **Spot:** Spot welding with adjustable spot diameter
- **Delay:** « Chain spot » function (Spot welding with time adjustment between 2 spots).

SYNERGIC MODE FOR EASY AND QUICK SETTINGS

- **With this function, the wire speed setting is Automatic.**

Simply select:

- the wire type
- the wire \varnothing
- the power

MONOGYS 200-2CS sets the optimum wire speed for you.

- **Save the last settings.**



Included :

- 1 torch 250 A (3m)
- Earth clamp (2m)

ACCESSORIES













Torch MB25 kit (250A) (Not included)



Ref. 041233

Composition:

- Contact tips:
 - \varnothing 0,8 M6 steel/stainless (x 5)
 - \varnothing 1,0 M6 steel/stainless (x 5)
 - \varnothing 1,0 M6 Alu (x 5)
- Contact tips supports 250A (x 3)
- Springs for nozzle (x 5)
- Nozzles 250A (x 3)

											
50/60hz	16A	min>max	GAS NO GAS	100 200 300	100 200 300	Electronic Control	équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica	EN60974-1 (40°C)	U ₀	cm/kg	Protected & compatible POWER GENERATOR (+/- 15%)
230V 1~	16A	30-200A	0.6 - 1.0	- -	- ✓ ✓		0.8/1.0 1.0	I _a (60%) X% (I ₂ max)	17V 34V	47x77x79 / 70	7.5 kVA