PROMIG 400 G.DV 230/400V - 3 Φ

Ref. 035904



3 Phase «Synergic» welding machine ideal for semi industrial work, maintenance and locksmith work. For use with separate wire feeder (TF 4R), the Trimig 400G is recommended for professional work up to Ø 1.2mm on steel, stainless-steel and aluminium. Easy and fast set up with its synergic control.

TRIGGER SETTING

2T: 2 stroke welding

■ 4T: 4 stroke welding, to weld during a long period

without constantly pressing the trigger

■ Spot : for plug welding

2 FUNCTIONS: MANUAL OR SYNERGIC

■ Synergic Mode: No need to adjust the wire speed. Microprocessor controlled, the machine automatically selects the optimum welding parameters.

Select::

- Wire Type
- · Wire diameter
- Power: 2 switches = 14 positions

PROMIG 400 G.DV automatically adjusts:

- Wire speed
- · Pre-gas and post-gas
- Burnback

Manual mode:


Manual setting of the wire speed.

Selection of the wire speed driver:

To switch the setting of the wire speed to or from separate wire feeder for a quick adjustment where required. External wire feeder ideal were access is difficult.

MADE IN FINANCE

| True | True



See TF 4R datasheetref. 033849

Delivered without wire feeder and accessories- Ref. 035904

| WELDING KIT: 035942 (no regulator) | | | | | | | | | | |
|------------------------------------|----------------------------------|---|--|--|--|--|--|--|--|--|
| | 4 | | 0 | | | | | | | |
| Promig 400 G.DV ref. 035904 | Wire feeder TF 4R ref. 033849 | Air cooled connection cable 10m – 70 mm² ref. 034860 | Earth clamps 4m - Ø 50 mm² ref. 043824 | Steel/stainless 350A – 4m (AIR) ref. 040946 | | | | | | |

| | 50/60hz | - AM - | | ⊕ ‡ | ømm | ⊕ ‡ _{ømm} | | © | équipé d'origine / original equipement / originalausstatung / equipamiento de fabrica | | EN60974-1 (40°C) | | ↓ /₽ | € | | |
|---|---------|------------------------------|---------|------------|-----------|---------------------------|-----|----------|--|---------|---------------------|-------------|----------------|-------------------|--|--|
| | | | min⊳max | GAS | NO GAS | 100 | 200 | 300 | Electronic Control | | ~ | IA (60%) | X% (I2 max) | cm/kg | Protected & compatible POWER GENERATOR (+/- 15%) | |
| - | 400V 3~ | 16A | 40-350A | 0.8 | | | ✓ | √ | 1 000→ | 1.0/1.2 | - | 270A | 350A 35% | 50x90x88 / 102 | 17 kVA | |
| | 230V 3~ | 25A | | 1.2 | - | | | | | | | | | | | |